



CRAFTING IDEA

GB

Deco knob Rose

WWW.RAYHER.COM



Used items:

36 051 000	Casting mould „Deco knobs	1 piece
36 029 000	Casting mould „Circle“	1 piece
36 052 000	Moulding Kit for knobs	1 bag
34 166 000	Jewellery cement	55 g
14 562 801	Large hole glass bead	1 piece
38 867 102	Chalky Finish	some
38 867 287	Chalky Finish	some
64 111 00	Round stick of beechwood	1 piece
69 078 000	Sandpaper	1 piece

Additionally you need:

Cooking oil, vessel to stir the cement, brush, wooden spatula

Instructions knob:

- 1 Place straight the casting mould „Deco knobs“ on the work surface and coat it with a cooking oil. For a safe standing position, you could use a towel or a sand bed.
- 2 Now, the screw set can be pre-mounted. For this purpose, you have to pull the screw through the holder and then tighten the nut so that the screw has an adequate size for the deco-cement knob. The screw height varies according to the subject height.
- 3 Stir 25 g of the jewellery-cement according to the package leaflet and pour it into the prepared casting mould. Position centrally the screw head.
- 4 Allow to dry for 24 hours.
- 5 The cast knob can now be removed by applying a slight pressure onto the back of the casting mould. Do not pull the screw! Clean the casting mould thoroughly with a detergent.
- 6 You can use the sandpaper to remove unwanted unevennesses or small ridges from the knob. Allow then the knob to dry thoroughly and paint it with the Chalky Finish colour.

Instructions small plate:

- 7 Place straight the casting mould „Circle“ on the work surface and coat it with a cooking oil. For a safe standing position, you could use a towel or a sand bed. Coat well the stick of beechwood with a cooking oil.
- 8 Stir 30 g of the jewellery-cement according to the package leaflet and pour it into the prepared casting mould. Place the holder (the spacer from the moulding kit) on the casting mould over the poured Circle and put the oiled stick of beechwood through the holder centrally in the cement.
- 9 Allow to dry for 24 hours.
- 10 The stick of beechwood can be removed from the cement-plate by careful turning. The cement-plate can now be removed by applying a slight pressure onto the back of the casting mould. Clean the casting mould thoroughly with a detergent.
- 11 You can use the sandpaper to remove unwanted unevennesses or small ridges from the small plate. Allow then the small plate to dry thoroughly and paint it with the Chalky Finish colour.

2+8



3+8



12



13





Completion:

12 Now you can mount the deco knob and attach it to your desired object. As small spacers you can put optionally one more large hole bead onto the screw between the knob and the small plate.

13 If the screw is too long for your drawer, you can easily pinch off the exceeding part using a suitable tool (e.g. the compound-leverage end cutter) and then sand it smooth.

Rayher.

KALEIDO 1 Brasov,

sos. Cristianului nr.1-3

KALEIDO 2 Brasov, str. Dr. Liviu Cimpeanu nr.47

Tel : 0726 244 171

Tel : 0726 244 174

www.rayherhobby.ro

www.kaleido.ro

